



iC 90

Fetal & Maternal
Monitor



iC 90 Fetal & Maternal Monitor



Features:

- Portable, easy operation & elegant design ;
- 12 inches TFT foldable color screen ;
- Basic parameters: FHR, TOCO, AFM, maternal SpO2, HR, NIBP, ECG, RESP, TEMP ;
- Advanced Digital Signal Processing (DSP) Technique is applied for Real-time Calculation and Mode Identification ;
- Help to improve efficiency by sorting out the traces that require closer analysis by obstetrician ;
- A standard patient event marker and a clinical event marking button to separately mark clinical events ;
- Provide convenience and reliability during antepartum, intrapartum and postpartum monitoring ;
- Continuous monitoring during transport ;
- Alarm system: time-over alarm, non-paper alarm, out of range FHR alarm ;
- High sensitivity FHR transducer, high signal-to-noise ratio ;
- 24 hours CTG storage, fast review and print ;
- Unique design for cable of transducers to avoid intertwinning ;
- Wire or wireless connect to central monitoring system ;
- Automatically adjust thermal paper 150mm/152mm ;
- High capability rechargeable Li-ion battery lasting 4 hours.

Options:

- Twins FHR measurement
- Build-in network/PC connecting interface
- FAS(fetal acoustic stimulator)
- Wireless network



Specification:

Fetal Heart Rate

Transducer: Multi-crystals, pulsed doppler
high sensitively

Strength: <5mW/cm²

Working frequency: 1.0MHz

Measurement range: 50~210 bpm

TOCO

Measurement range: 0~100 units

Auto Fetal Movement (AFM): Automatic detection

SpO₂

Measurement range : 70%~100%。

Accuracy: ±3%

HR

Measurement range: 30bpm~240bpm

Accuracy: ±2 bpm

NIBP

Systolic pressure: 50~240mmHg

Diastolic pressure: 25~200mmHg

Mean pressure: 15~180mmHg

Measure mode: Manual

ECG

Heart Rate Measurement and

Alarm Range: 15-300bpm

Accuracy: ±1bpm

Input: 5-lead ECG cable

Sweep Speed: 25 mm/s

Amplitude Selection: x1/4, x1/2, x1, x2, x4

Temperature

Measurement and Alarm Limit: 0-50°C

Probe: Skin surface

Accuracy: ±0.1°C(25°C ~45°C),

±0.2°C(0°C ~25°C or 45°C ~50°C)

Respiration

Measurement Mode: Thoracic Impedance

Respiration Rate: 0-150 bpm

Waveform Display Speed: 25mm/s

Power: A.C.100-240v, 50/60Hz or 16.8v Li-ION battery

Power Consumption: < 20W

Dimension: 350mm×320mm×85mm (LxWxH)

Net weight:3.5 kg